

Valvonnan tekniset tiedot

Yksityismallisto

Kaupallinen mallisto

Teollinen mallisto

Vulcan 3000



Vulcan 5000



Vulcan S10



Vulcan S25



Vulcan S100



Vulcan S250



Vulcan S500



Max. putken halkaisija	1½" 38 mm	2" 50 mm	3" 76 mm	4" 100 mm	6" 150 mm	10" 250 mm	20" 500 mm
Max. Kapasiteetti	3000 l/h	5000 l/h	10 m³/h	25 m³/h	100 m³/h	250 m³/h	500 m³/h
Jännite	24 Volt	24 Volt	24 Volt	24 Volt	24 Volt	24 Volt	24 Volt
Teho	2,0 W	2,0 W	2,25 W	2,25 W	2,5 W	2,75 W	3,25 W
Impulssikaapeli	2 x 1 m	2 x 1 m	2 x 1 m	4 x 2 m	6 x 4 m	8 x 10 m	10 x 30 m
Kaistaleveys	10 mm	10 mm	20 mm	20 mm	20 mm	20 mm	20 mm
Mitat	80/130/30 mm	85/150/30 mm	120/190/40 mm	125/200/40 mm	150/240/40 mm	200/295/50 mm	220/320/50 mm
Taajuusalue	3-32 kHz	3-32 kHz	3-32 kHz	3-32 kHz	3-32 kHz	3-32 kHz	3-32 kHz
Tarvittava tila	300 mm	350 mm	500 mm	600 mm	1200 mm	2500 mm	5000 mm
Ohjelmia	1	1	3	5	10	10	10