

Vulcan

Technical Data Overview



	Private Line		Commercial Line			Industrial Line	
	Vulcan 1000	Vulcan 5000	Vulcan S10	Vulcan S25	Vulcan S100	Vulcan S250	Vulcan S500
Capacity	1000 l/h	5000 l/h	10 m ³ /h	25 m ³ /h	100 m ³ /h	250 m ³ /h	500 m ³ /h
Maximum pipe diameter	1" (~25 mm)	2" (~50 mm)	3" (~76 mm)	4" (~100 mm)	6" (~150 mm)	10" (~250 mm)	20" (~500 mm)
Voltage	24 volt	24 volt	24 volt	24 volt	24 volt	24 volt	24 volt
Wattage	1.75 Watt	2.0 Watt	2.25 watt	2.25 watt	2.5 Watt	2.75 Watt	3.25 Watt
Impulse bands	2 x 0.5 m	2 x 1 m	2 x 1 m	4 x 2 m	6 x 4 m	8 x 10 m	10 x 30 m
Measurements mm	60/90/30	85/150/30	110/170/35	125/200/35	160/200/40	205/295/45	225/325/45
Frequency range	3-32 KHz	3-32 KHz	3-32 KHz	3-32 KHz	3-32 KHz	3-32 KHz	3-32 KHz
Required space	200 mm	350 mm	500 mm	600 mm	1200 mm	2500 mm	5000 mm
Programs	0	0	3	5	10	10	10

Electronic Switching power supply unit

In	87-260 Volt 50-60 Hz	87-260 Volt 50-60 Hz	87-260 Volt 50-60 Hz	87-260 Volt 50-60 Hz	87-260 Volt 50-60 Hz	87-260 Volt 50-60 Hz	87-260 Volt 50-60 Hz
Out	24 Volt 600 mA	24 Volt 600 mA	24 Volt 600 mA	24 Volt 600 mA	24 Volt 600 mA	24 Volt 600 mA	24 Volt 600 mA